

SD1 Desktop Kit 250

SD1 Desktop Kit
250



Specifications: SD1 Desktop Kit 250 Mounting hardware included

Nominal Impedance	8 ohm
Impedance (min)	7.8 ohm
Frequency Response (\pm 0.25 dB)	60 - 15,000 Hz Nominal w/o EQ
Max. Program Power	100 W
Max. Continuous Power RMS	30 W
Max. Power SPL @ 1 M	88.5 dB
Enclosure - material	Chrome plated aluminum
Grille - material	N/A
Height (SM = Height)	2.02 in / 51.3 mm
Diameter (SM = Width)	2.30 in / 58.4 mm
Weight	.67 kg / 1.5 lbs
Shipping Weight	/ 4.3 lbs

SD1 Desktop Kit 250

SD1 Desktop Kit
250



Description

The SolidDrive SD1 Desktop Kit-250 is the ideal way to see how the SolidDrive works on any surface. The SolidDrive unit in the kit has a special silicon backing so it will work with virtually any surface without scratching or leaving a mark. The kit is also includes the SD-250 amplifier. This is a 50 watts rms per channel amplifier that can run in stereo, mono, or bridged with balanced or unbalanced inputs. But most importantly it has custom electronic EQs for glass, sheet rock, wood, or bypass. Having the correct power and the right EQ will make the AD sound its best.

Patented SolidDrive Technologies

SolidDrive and MSE Audio Group constantly develop new technologies that enhance audio product performance. SolidDrive innovations are protected by multiple U.S. and international patents, which explicitly cover SolidDrive dispersion, enclosure and dome technologies. MSE

Audio Group actively defends its patents in order to protect SolidDrive resellers and end users.

Technical Data and Specification Tools

Technical Data

SolidDrive strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SolidDrive speakers are independently collected from and verified by NWAALabs

(www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

SolidDrive

8005 W. 110th St. / Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax
Toll Free 855.663.5600
<http://soliddrive.mseaudio.com>
All SolidDrive products come with a 5-year limited warranty.

SD1 Desktop Kit 250

SD1 Desktop Kit
250



Included Accessories

SD-250 Amplifier



Passive EQ Modules