

IW200

Dual 8" In-Wall Subwoofer with Sealed Enclosure

SolidDrive
INVISIBLE SOUND SOLUTIONS



Specifications: IW200

Mounting hardware included

Nominal Impedance	4 Ohms
Impedance (min)	4 Ohms
Frequency Response (1)	25 Hz - 160 Hz
Frequency Response (± 3 dB)	25 Hz - 160 Hz
Recommended Power	350 Watts
Transducer - Low Frequency Driver	(2x) 8" Mica-Graphite Polypropylene w/ NBR Surround
Enclosure alignment	Sealed
Grille - material	White Powder-Coated Galvanized Magnetic Micro-Flange (Paintable)
Grille - part	White Powder-Coated Galvanized Magnetic Micro-Flange (Paintable)
Height (SM = Height)	1828.8 mm / 72"
Diameter (SM = Width)	365.8 mm / 14.4"
Cutout Height (Surface Mount Height)	520.7 mm / 20.5"
Cutout Width/Diameter	222.3 mm / 8.75"
Mounting Hole Diameter	Enclosure mounts between 16" on-center 2" x 4" studded wall
Mounting Depth	Enclosure mounts between 16" on-center 2" x 4" studded wall
Weight	27.2 kg / 60 lbs (Subwoofer and Back box)
Shipping Weight	29.5 kg / 65 lb

Description

Create deep, accurate bass without altering a room's design. Easily mount between standard wall studs. Contains patented subwoofer technology. Blend into any room's decor. Combine with the SolidDrive to create the ultimate "in-wall" home theater system.**

The IW-200 is an in-wall subwoofer with a sealed enclosure. The sub enclosure box mounts easily between 16" on-center wall studs, and its vibration-isolating outer foam layer virtually eliminates the risk of buzzing and wall rattling. Recommended for rooms up to 3,300 cubic feet in volume. Larger rooms can simply use multiple IW-200 subwoofers.

Features a 7-year warranty.

Patented SolidDrive Technologies

SolidDrive and MSE Audio Group constantly develop new technologies that enhance audio product performance. SolidDrive innovations are protected by multiple U.S. and

international patents, which explicitly cover SolidDrive dispersion, enclosure and dome technologies. MSE Audio Group actively defends its patents in order to protect SolidDrive resellers and end users.

Technical Data and Specification Tools

Technical Data

SolidDrive strives to provide complete and effective technical information and data to dealers, engineers and designers. All data are available from SoundTube Entertainment or at www.soundtube.com. Technical data and downloads include: EASE™ data - 3-D polar plots. EASE™ Address - 2-D modeling for distributed systems Autodesk® Revit® software Tech Sheets - Technical information and architectural specs for system engineers SoundTubeSPEC™ - Proprietary speaker placement software

Data Acquisition and Verification

All data for SolidDrive speakers are independently collected from and verified

by NWAALabs (www.nwaalabs.com) using their proprietary MACH testing system. All data are collected and analyzed according to ASTM, ISO and AES standards using EASRA, TEF and MLSSA. Full balloon data including both phase and magnitude are compiled into a variety of formats including EASE 4.x, GLL and CLF.

Architectural Specifications

No specifications currently.

SolidDrive

8005 W. 110th St. / Suite 208
Overland Park, KS 66210
Phone 913.663.5600
Fax
Toll Free 855.663.5600
<https://soliddrive.mseaudio.com>
All SolidDrive products come with a 5-year limited warranty.

IW200

Dual 8" In-Wall Subwoofer with
Sealed Enclosure

SolidDrive
INVISIBLE SOUND SOLUTIONS
